



CONSTRUCTION NOTES:

- ① 8" x 4" SDR-35 PVC wye (F x M x F).
- ② 4" SDR-35 PVC 22.5° bend (F x M).
- ③ Incoming 4" lateral per applicable portions of STD-406-L.
- ④ Frame & cover shall be Brooks product No. 4TT marked "sewer" per applicable portions of STD-511-L.
- ⑤ 8" SDR-35 PVC 45° bend (F x M).
- ⑥ 8" x 8" SDR-35 PVC wye (F x F x F).
- ⑦ 8" SDR-35 PVC pipe.
- ⑧ 8" Rubber mechanical banded seal clamp. Fernco or City approved equal.

GENERAL NOTES:

- 1. Up to four residential wyes per chimney will be permitted depending on sewer main depth.
- 2. Chimney installation is only permitted under the special approval of Utilities Department.
- 3. Commercial laterals may not be stacked on a chimney with other laterals.
- 4. PVC pipe and fittings shall be bedded with ¾" crushed rock material. In areas of ground water or tide water ⅝" crushed rock.

CITY OF NEWPORT BEACH
PUBLIC WORKS DEPARTMENT

**SEWER LATERAL
CHIMNEY CONNECTION(S)**

APPROVED:

PUBLIC WORKS DIRECTOR

RCE NO. 36106

Drawn: M. Elias

Date: Jan. 2004

Scale: N.T.S.

F:\USERS\PBW\Shared\CAD_STD\STD Details\2003_Std\STD Sewer

DRAWING NO.

STD-408-L