



**NOTES:**

1. WHEN REMOVING EXISTING SIDEWALK AND CURB AND GUTTER, SAWCUT AND REMOVE TO NEAREST EXISTING JOINT WITHIN 5 FEET BEYOND CURB OPENING.
2. SLOPED "X" AREAS AND SLOPE DRIVEWAYS SHALL HAVE A COARSE BROOM FINISH.
3. CONCRETE SHALL BE 560-C-3250.
4. "W" SHALL BE MINIMUM OF 10 FEET AND A MAXIMUM OF 20 FEET EXCEPT IN THE CASE OF THREE CAR GARAGE WHERE "W" MAY EQUAL 25 FEET OR 32 FEET FOR A 4 CAR GARAGE.
5. "W" SHALL BE CENTERED WITH GARAGE OPENING.

FORMER CITY STANDARD PLAN NUMBER (2004 EDITION): STD 162-L

APP. <i>James M. Hinkle</i>	51568	11/24/2020			
CITY ENGINEER	RCE	DATE	NO.	DATE	DESCRIPTION OF REVISIONS

**CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS**

DRAWN: P. KHARAZMI  
DATE: 11/3/2020

**RESIDENTIAL DRIVEWAY APPROACH TYPE I**

STANDARD DRAWING NO.  
**162**  
SHEET 1 OF 1