



NOTES:

1. LOCATION OF WATER MAIN WILL GOVERN THE LOCATION OF UTILITIES. NORMALLY THE WATER MAIN WILL BE LOCATED ON THE NORTH OR EAST SIDE OF THE STREET.
2. PROVIDE 36" MIN OF COVER FROM FINISHED GRADE FOR 12" AND SMALLER MAINS. MAINS LARGER THAN 12", MAINS IN ARTERIAL STREETS, P.V.C., H.D.P.E. AND OTHER FLEXIBLE PIPE REQUIRE SPECIAL DESIGN.
3. STREET LIGHTS MAY BE LOCATED AT BACK OF WALK WHEN SIDEWALK IS ADJACENT TO THE CURB, UPON APPROVAL OF THE PUBLIC WORKS DEPARTMENT.
4. UTILITY VENT PIPES, METER SERVICE POINTS AND ANY OTHER ABOVE-GROUND FACILITIES SHALL BE INSTALLED IN THE UNPAVED PARKWAY OR AT THE BACK OF SIDEWALK.

APP.	51568 CITY ENGINEER RCE	11/24/2020 DATE	
			NO. DATE DESCRIPTION OF REVISIONS

CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS

DRAWN: P. KHARAZMI
DATE: 11/3/2020

STANDARD LOCATIONS OF UNDERGROUND UTILITIES

STANDARD DRAWING NO.
101
SHEET 1 OF 1