

CONSTRUCTION NOTES

- (1) DOUBLE CHECK BACKFLOW DEVICE. REFER TO UNIVERSITY OF SOUTHERN CALIFORNIA FOUNDATION FOR CROSS-CONNECTION AND HYDRAULIC RESEARCH APPROVED LIST (WWW.USC.EDY/DEPT/FCCCHR/LIST.HTML) AND STD 519-A FOR DETAILS.
- WATER SYSTEM SERVICE METER. REFER TO STD 502 & STD 503 FOR DETAILS.
- (3) FIRE SYSTEM SERVICE METER. REFER TO STD 526 FOR DETAILS.
- 1" OR 2" BALL CORP. STOP F600-4 WITH MIP THREAD INLET & OUTLET. JAMES JONES J-1943 OR FORD FB-500.
- DOUBLE STRAP BRONZE SERVICE CLAMP WITH IPT OUTLET. JAMES JONES J-979 OR FORD 202B. REFER TO STD 502 FOR WATER MAIN TAP DETAILS. WRAP IN 10 MIL THICK PLASTIC SHEETING.
- (6) 1" OR 2" WROT COPPER TEE WITH FEMALE SOLDER ENDS. ¾"-1" FLARE T.
- (7) FOR 11/2" SERVICE, OR GREATER, MUST HAVE 2" FIP X FIP COUPLING, MADE IN USA.

		tout my the life.					
APP.		In the American	 51568 11/24/2	020			
		CITY ENGINEER	RCE DATI		NO.	DATE	DESCRIPTION OF REVISIONS
	CITY OF NEWPORT BEACH DEPARTMENT OF PUBLIC WORKS						

M. ELIAS DRAWN:

DATE: 11/3/2020 3/4" - 2" JR. FIRE SYSTEM SERVICE TYPE 2

STANDARD DRAWING NO.